



SAFETY DATA SHEET

SDS PREP DATE: 8/30/2017

SDS REVISION DATE: 6/21/2017

3137 E. 26th Street
Vernon, CA 90058
(323) 266-7111

Product ID: 57011

24-Hour Emergency Telephone: (800) 255-3924

This Safety Data Sheet contains environmental, health and toxicology information for your employees. Please make sure this information is given to them. It also contains information to help you meet community Right To Know emergency response reporting requirements under SARA TITLE III and many other laws. If you resell this product, this SDS must be given to the buyer or the information incorporated in your SDS.

Section 1: Company and Product Identification

Starco Brands
3137 E. 26th Street
Vernon, CA 90058
(323) 266-7111

24-Hour Emergency Telephone: (800) 255-3924

Product ID: 57011

Product Name: Breathe - Bathroom Cleaner (6 x 14 oz)

Intended Use: CLEANER

Section 2: Hazard(s) Identification

Product Signal Word: **WARNING**

Physical Hazard Classification: Aerosols, Category 3

Contains gas under pressure; may explode if heated.

Physical Hazard Precautionary Statements:

Do not pierce or burn, even after use.

Do not expose to temperatures exceeding 50 °C/122°F.



Section 3: Product Composition

	CAS#	% Range		PEL	TLV
NITROGEN	7727-37-9	1%	10%	N/D	N/D
CITRIC ACID	72-92-9	0%	3%	5.00 mg/m3	5.00 mg/m3
INERT MATERIAL	7732-18-5	75%	99%	N/D	N/D
DIPROPYLENE GLYCOL METHYL	34590-94-8	0%	3%	100 PPM SKIN	100 PPM SKIN

Specific chemical identity and exact percentages are withheld as Trade Secret.

Section 4: First-Aid Measures

GENERAL: This material is an aspiration hazard and defats the skin. Breathing vapors of high concentrations may cause CNS depression.

EYE CONTACT: Slightly irritating but does not injure eye tissue.

SKIN CONTACT: Low order of toxicity. Frequent or prolonged contact may irritate and cause dermatitis. Skin contact may aggravate an existing dermatitis condition.

INHALATION: High vapor/aerosol concentrations (greater than approximately 100 ppm) are irritating to the eyes and the respiratory tract, may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death.

INGESTION: Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury,



SAFETY DATA SHEET

SDS PREP DATE: 8/30/2017

SDS REVISION DATE: 6/21/2017

3137 E. 26th Street
Vernon, CA 90058
(323) 266-7111

Product ID: 57011

24-Hour Emergency Telephone: (800) 255-3924

possibly minimal toxicity.

FIRST AID
EYE CONTACT: Flush eyes with large amounts of water until irritation subsides. If irritation persists, get medical attention.
SKIN CONTACT: Flush with large amounts of water; use soap if available. Remove grossly contaminated clothing, including shoes, and launder before reuse.
INHALATION: Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Call for prompt medical attention
INGESTION: If swallowed, DO NOT induce vomiting. Keep at rest. Get prompt medical attention.

PRECAUTIONS
SPECIAL PRECAUTIONS: Health studies have shown that many hydrocarbons pose potential human health risks which may vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized.
PERSONAL PROTECTION: For open systems where contact is likely, wear safety glasses with side shields, long sleeves, and chemical resistant gloves. Where concentrations in air may exceed the limits, work practice or other means of exposure reduction are not adequate, NIOSH/MSHA approved respirators may be necessary to prevent overexposure by inhalation.
VENTILATION: The use of mechanical dilution ventilation is recommended whenever this product is used in a confined space, is heated above ambient temperatures, or is agitated.

Section 5: Fire-Fighting Measures

FIRE AND EXPLOSION HAZARDS: This product releases Flammable Vapors at well below ambient temperatures and readily forms flammable mixtures with air exposed to an ignition source. It will burn in the open or be explosive in confined spaces. Its vapors are heavier than air and may travel long distances to a point of ignition, and then flash back. Alkaline/chlorine gas mixtures have produced explosions.

EXTINGUISHING MEDIA: Dry Chemical. CO2. Halogenated Extinguishing Agent. Stop Gas Flow.

SPECIAL FIREFIGHTING PROCEDURES: Gas fires should not be extinguished unless the gas flow can be stopped immediately. Allow the fire to burn itself out. If the source cannot be shut off immediately, all equipment and surfaces exposed to the fire should be cooled with water to prevent over-heating flash-backs, or explosions. Control fire until gas supply can be shut off. Use proper protective equipment. Use fresh air respirator when exposure to hazardous concentrations of toxic gases is possible.

FIRE FIGHTING: Use water spray to cool fire exposed surfaces and to protect personnel. Isolate "fuel" supply from fire. Use foam, dry chemical, or water spray to extinguish fire. Avoid spraying water directly into storage containers due to danger of boiling over. This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode.

Section 6: Accidental Release Measures

STEPS TO BE TAKEN IN CASE CONTAINER IS PUNCTURED AND MATERIAL IS RELEASED:
Clean up area by mopping or with absorbent materials and place in closed container for disposal. Consult Federal, State, and local disposal authorities.

WASTE DISPOSAL METHOD: Consult local authorities for proper waste disposal procedures. Empty de-pressurized containers can not be reused. Cans which are pressurized or contain liquid must be disposed of in a permitted waste management facility. Consult Federal, State, and local disposal authorities for approved procedures.

Section 7: Handling and Storage

VENTILATION REQUIREMENT: Use adequate level exhaust ventilation. Note: Where carbon monoxide may be generated, special ventilation may be required. Local exhaust recommended when appropriate to control employee exposure.

RESPIRATORY PROTECTION: Based on contamination level and working limits of the respirator, use a respirator approved by NIOSH/MSHA.

EYES: Face shield and goggles or chemical goggles should be worn.



SAFETY DATA SHEET

SDS PREP DATE: 8/30/2017

SDS REVISION DATE: 6/21/2017

3137 E. 26th Street
Vernon, CA 90058
(323) 266-7111

Product ID: 57011

24-Hour Emergency Telephone: (800) 255-3924

GLOVES: Impervious gloves should be worn. Gloves contaminated with the product should be discarded. Polyfluorinated polyethylene has been suggested.

OTHER CLOTHING EQUIPMENT: Standard work clothing. Standard work shoes; discard if shoes can not be decontaminated. Store contaminated clothing in well ventilated cabinets or closed containers. Wash contaminated clothing and dry before reuse.

RESPIRATORY PROTECTION: In situations where vapor concentrations exceed the recommended exposure limits, a NIOSH approved organic vapor cartridge or air-supplying respirator should be worn.

Section 8: Exposure Control / Personal Protection

VENTILATION REQUIREMENT: Use adequate level exhaust ventilation. Note: Where carbon monoxide may be generated, special ventilation may be required. Local exhaust recommended when appropriate to control employee exposure.

RESPIRATORY PROTECTION: Based on contamination level and working limits of the respirator, use a respirator approved by NIOSH/MSHA.

EYES: Face shield and goggles or chemical goggles should be worn.

GLOVES: Impervious gloves should be worn. Gloves contaminated with the product should be discarded. Polyfluorinated polyethylene has been suggested.

OTHER CLOTHING EQUIPMENT: Standard work clothing. Standard work shoes; discard if shoes can not be decontaminated. Store contaminated clothing in well ventilated cabinets or closed containers. Wash contaminated clothing and dry before reuse.

RESPIRATORY PROTECTION: In situations where vapor concentrations exceed the recommended exposure limits, a NIOSH approved organic vapor cartridge or air-supplying respirator should be worn.

Section 9: Product Properties

Flash Point (CCP): N/A

Boiling Point for Product: N/D

Vapor Pressure for Product: N/D

Vapor Density for Product: N/D

Specific Gravity: N/D

V.O.C.: <1% by weight

Water Solubility: SOLUBLE

Appearance: AEROSOL SPRAY

PH: NEUTRAL

Section 10: Stability and Reactivity

STABILITY: Stable

CONDITIONS TO AVOID: Temperatures above 130 degree F.

HAZARDOUS POLYMERIZATION: Will not occur



SAFETY DATA SHEET

SDS PREP DATE: 8/30/2017

SDS REVISION DATE: 6/21/2017

3137 E. 26th Street
Vernon, CA 90058
(323) 266-7111

Product ID: 57011

24-Hour Emergency Telephone: (800) 255-3924

MATERIALS AND CONDITIONS TO AVOID INCOMPATIBILITY: Strong oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: None

Section 11: Toxicological Information

CITRIC ACID 72-92-9

Routes of Entry: Inhalation. Ingestion.

Toxicity to Animals: Acute oral toxicity (LD50): 3000 mg/kg [Rat].

Chronic Effects on Humans: May cause damage to the following organs: teeth.

Other Toxic Effects on Humans: Hazardous in case of inhalation (lung irritant). Slightly hazardous in case of skin contact (irritant, sensitizer), of ingestion.

DIPROPYLENE GLYCOL METHYL ETHER 34590-94-8

Acute oral toxicity: LD 50 rat: 5200mg/kg

Acute dermal toxicity: LC 75 rabbit: 5900mg/kg

EFFECTS ACUTE EXPOSURE

SKIN CONTACT: little to no effect

SKIN ABSORPTION: yes, no toxic effects unlikely by this route

EYE CONTACT: slightly irritating, will not damage eyes

INHALATION: vapor concentrations above 100ppm may irritate respiratory tract; low vapor pressure makes development of such a concentration unlikely in an industrial setting

INGESTION: may cause stomach discomfort; may cause diarrhoea; a massive dose (say, 100ml) would be required to produce any symptoms in a human of average weight

EFFECTS OF CHRONIC EXPOSURE

GENERAL: prolonged deliberate exposure may cause skin cracking and dermatitis

SENSITISING: not a sensitizer

REPRODUCTIVE EFFECT: no known effect on humans or animals

SYNERGISTIC WITH: not known

Section 12: Ecological Information

CITRIC ACID 72-92-9

Products of Biodegradation: Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

Toxicity of the Products of Biodegradation: The product itself and its products of degradation are not toxic.

DIPROPYLENE GLYCOL METHYL ETHER 34590-94-8

This product cannot accumulate in living tissue; this product is readily and rapidly biodegradeable in the presence of oxygen

If applicable, IARL, NPT and OSHA carcinogens and chemicals subject to the reporting requirements of SARA Title III, Section 313 are identified in Section III with an "*". Additional ecological information is Not Determined.

Section 13: Disposal Information

WASTE DISPOSAL METHOD: Consult local authorities for proper waste disposal procedures. Empty de-pressurized containers can not be reused. Cans which are pressurized or contain liquid must be disposed of in a permitted waste management facility. Consult Federal, State, and local disposal authorities for approved procedures.

Section 14: Transportation Information

SDS PREP DATE: 8/30/2017

SDS REVISION DATE: 6/21/2017



SAFETY DATA SHEET

SDS PREP DATE: 8/30/2017

SDS REVISION DATE: 6/21/2017

3137 E. 26th Street
Vernon, CA 90058
(323) 266-7111

Product ID: 57011

24-Hour Emergency Telephone: (800) 255-3924

DOT Proper Shipping Name: UN1950

Aerosols, non-flammable, (each not exceeding 1L
capacity) 2.2

Section 15: Regulatory Information

	CAS#	PEL	TLV
NITROGEN	7727-37-9	N/D	N/D
CITRIC ACID	72-92-9	5.00 mg/m3	5.00 mg/m3
INERT MATERIAL	7732-18-5	N/D	N/D
DIPROPYLENE GLYCOL METHYL	34590-94-8	100 PPM SKIN	100 PPM SKIN

If applicable, IARL, NPT and OSHA carcinogens and chemicals subject to the reporting requirements of SARA Title III, Section 313 are identified above with an "*"

Section 16: Other Information

Consumer Product Safety Act Certification.

This product was evaluated by the Company listed above and is certified to be in compliance with the provisions of the Consumer Product Safety Act, the Federal Hazardous Substances Act, and the Poison Prevention Packaging Act, as applicable. This product was manufactured at the location identified on the SDS. The date of manufacture is stamped on the product container. No testing is required to certify compliance with the above mentioned regulation.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.



SAFETY DATA SHEET

3137 E. 26th Street
Vernon, CA 90058
(323) 266-7111

SDS PREP DATE: 8/30/2017

SDS REVISION DATE: 6/21/2017

Product ID: 57012

24-Hour Emergency Telephone: (800) 255-3924

This Safety Data Sheet contains environmental, health and toxicology information for your employees. Please make sure this information is given to them. It also contains information to help you meet community Right To Know emergency response reporting requirements under SARA TITLE III and many other laws. If you resell this product, this SDS must be given to the buyer or the information incorporated in your SDS.

Section 1: Company and Product Identification

Starco Brands
3137 E. 26th Street
Vernon, CA 90058
(323) 266-7111

24-Hour Emergency Telephone: (800) 255-3924

Product ID: 57012

Product Name: Breathe - Multi Purpose Cleaner (6 x 14 oz)

Intended Use: CLEANER

Section 2: Hazard(s) Identification

Product Signal Word: **WARNING**

Physical Hazard Classification: Aerosols, Category 3

Contains gas under pressure; may explode if heated.

Physical Hazard Precautionary Statements:

Do not pierce or burn, even after use.

Do not expose to temperatures exceeding 50 °C/122°F.



Section 3: Product Composition

	CAS#	% Range		PEL	TLV
NITROGEN	7727-37-9	1%	10%	N/D	N/D
INERT MATERIAL	7732-18-5	75%	99%	N/D	N/D
SODIUM BENZOATE	532-32-1	0%	3%	<NOT ESTABLISHED>	<NOT ESTABLISHED>
PROPYLENE GLYCOL	57-55-6	1%	5%	<NONE ESTABLISHED>	<NONE ESTABLISHED>

Specific chemical identity and exact percentages are withheld as Trade Secret.

Section 4: First-Aid Measures

GENERAL: This material is an aspiration hazard and defats the skin. Breathing vapors of high concentrations may cause CNS depression.

EYE CONTACT: Slightly irritating but does not injure eye tissue.

SKIN CONTACT: Low order of toxicity. Frequent or prolonged contact may irritate and cause dermatitis. Skin contact may aggravate an existing dermatitis condition.

INHALATION: High vapor/aerosol concentrations (greater than approximately 100 ppm) are irritating to the eyes and the respiratory tract, may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death.

INGESTION: Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury,



SAFETY DATA SHEET

SDS PREP DATE: 8/30/2017

SDS REVISION DATE: 6/21/2017

3137 E. 26th Street
Vernon, CA 90058
(323) 266-7111

Product ID: 57012

24-Hour Emergency Telephone: (800) 255-3924

possibly minimal toxicity.

FIRST AID
EYE CONTACT: Flush eyes with large amounts of water until irritation subsides. If irritation persists, get medical attention.
SKIN CONTACT: Flush with large amounts of water; use soap if available. Remove grossly contaminated clothing, including shoes, and launder before reuse.
INHALATION: Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Call for prompt medical attention
INGESTION: If swallowed, DO NOT induce vomiting. Keep at rest. Get prompt medical attention.

PRECAUTIONS
SPECIAL PRECAUTIONS: Health studies have shown that many hydrocarbons pose potential human health risks which may vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized.
PERSONAL PROTECTION: For open systems where contact is likely, wear safety glasses with side shields, long sleeves, and chemical resistant gloves. Where concentrations in air may exceed the limits, work practice or other means of exposure reduction are not adequate, NIOSH/MSHA approved respirators may be necessary to prevent overexposure by inhalation.
VENTILATION: The use of mechanical dilution ventilation is recommended whenever this product is used in a confined space, is heated above ambient temperatures, or is agitated.

Section 5: Fire-Fighting Measures

FIRE AND EXPLOSION HAZARDS: This product releases Flammable Vapors at well below ambient temperatures and readily forms flammable mixtures with air exposed to an ignition source. It will burn in the open or be explosive in confined spaces. Its vapors are heavier than air and may travel long distances to a point of ignition, and then flash back. Alkaline/chlorine gas mixtures have produced explosions.

EXTINGUISHING MEDIA: Dry Chemical. CO2. Halogenated Extinguishing Agent. Stop Gas Flow.

SPECIAL FIREFIGHTING PROCEDURES: Gas fires should not be extinguished unless the gas flow can be stopped immediately. Allow the fire to burn itself out. If the source cannot be shut off immediately, all equipment and surfaces exposed to the fire should be cooled with water to prevent over-heating flash-backs, or explosions. Control fire until gas supply can be shut off. Use proper protective equipment. Use fresh air respirator when exposure to hazardous concentrations of toxic gases is possible.

FIRE FIGHTING: Use water spray to cool fire exposed surfaces and to protect personnel. Isolate "fuel" supply from fire. Use foam, dry chemical, or water spray to extinguish fire. Avoid spraying water directly into storage containers due to danger of boiling over. This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode.

Section 6: Accidental Release Measures

STEPS TO BE TAKEN IN CASE CONTAINER IS PUNCTURED AND MATERIAL IS RELEASED:
Clean up area by mopping or with absorbent materials and place in closed container for disposal. Consult Federal, State, and local disposal authorities.

WASTE DISPOSAL METHOD: Consult local authorities for proper waste disposal procedures. Empty de-pressurized containers can not be reused. Cans which are pressurized or contain liquid must be disposed of in a permitted waste management facility. Consult Federal, State, and local disposal authorities for approved procedures.

Section 7: Handling and Storage

VENTILATION REQUIREMENT: Use adequate level exhaust ventilation. Note: Where carbon monoxide may be generated, special ventilation may be required. Local exhaust recommended when appropriate to control employee exposure.

RESPIRATORY PROTECTION: Based on contamination level and working limits of the respirator, use a respirator approved by NIOSH/MSHA.

EYES: Face shield and goggles or chemical goggles should be worn.



SAFETY DATA SHEET

SDS PREP DATE: 8/30/2017

SDS REVISION DATE: 6/21/2017

3137 E. 26th Street
Vernon, CA 90058
(323) 266-7111

Product ID: 57012

24-Hour Emergency Telephone: (800) 255-3924

GLOVES: Impervious gloves should be worn. Gloves contaminated with the product should be discarded. Polyfluorinated polyethylene has been suggested.

OTHER CLOTHING EQUIPMENT: Standard work clothing. Standard work shoes; discard if shoes can not be decontaminated. Store contaminated clothing in well ventilated cabinets or closed containers. Wash contaminated clothing and dry before reuse.

RESPIRATORY PROTECTION: In situations where vapor concentrations exceed the recommended exposure limits, a NIOSH approved organic vapor cartridge or air-supplying respirator should be worn.

Section 8: Exposure Control / Personal Protection

VENTILATION REQUIREMENT: Use adequate level exhaust ventilation. Note: Where carbon monoxide may be generated, special ventilation may be required. Local exhaust recommended when appropriate to control employee exposure.

RESPIRATORY PROTECTION: Based on contamination level and working limits of the respirator, use a respirator approved by NIOSH/MSHA.

EYES: Face shield and goggles or chemical goggles should be worn.

GLOVES: Impervious gloves should be worn. Gloves contaminated with the product should be discarded. Polyfluorinated polyethylene has been suggested.

OTHER CLOTHING EQUIPMENT: Standard work clothing. Standard work shoes; discard if shoes can not be decontaminated. Store contaminated clothing in well ventilated cabinets or closed containers. Wash contaminated clothing and dry before reuse.

RESPIRATORY PROTECTION: In situations where vapor concentrations exceed the recommended exposure limits, a NIOSH approved organic vapor cartridge or air-supplying respirator should be worn.

Section 9: Product Properties

Flash Point (CCP): N/A, LVL 1 NON-FLAMMABLE AEROSOL

Boiling Point for Product: N/D

Vapor Pressure for Product: N/D

Vapor Density for Product: N/D

Specific Gravity: N/D

V.O.C.: 0% by weight

Water Solubility: SOLUBLE

Appearance: AEROSOL SPRAY

PH: N/D

Section 10: Stability and Reactivity

STABILITY: Stable

CONDITIONS TO AVOID: Temperatures above 130 degree F.

HAZARDOUS POLYMERIZATION: Will not occur



STARCO BRANDS

SAFETY DATA SHEET

SDS PREP DATE: 8/30/2017

SDS REVISION DATE: 6/21/2017

3137 E. 26th Street
Vernon, CA 90058
(323) 266-7111

Product ID: 57012

24-Hour Emergency Telephone: (800) 255-3924

MATERIALS AND CONDITIONS TO AVOID INCOMPATIBILITY: Strong oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: None

Section 11: Toxicological Information

SODIUM BENZOATE 532-32-1

Acute oral toxicity: LD 50 Rat: 4070 mg/kg

May aggravate existing skin conditions, exposure may cause redness and irritation to skin, respiratory system, eyes, and gastrointestinal tract.

PROPYLENE GLYCOL 57-55-6

Acute oral toxicity: LD50 (rabbit): 18500 mg/kg

Acute dermal toxicity: LD50 (rabbit): 20800 mg/kg

Routes of Entry: Absorbed through skin. Eye contact.

Chronic Effects on Humans: May cause damage to the following organs: central nervous system (CNS).

Other Toxic Effects on Humans:

Hazardous in case of ingestion. Slightly hazardous in case of skin contact (irritant, permeator), of inhalation.

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans:

May affect genetic material (mutagenic). May cause adverse reproductive effects and birth defects (teratogenic) based on animal test data.

Special Remarks on other Toxic Effects on Humans: Acute Potential Health Effects: Skin: May cause mild skin irritation. It may be absorbed through the skin and cause systemic effects similar to those of ingestion. Eyes: May cause mild eye irritation with some immediate, transitory stinging, lacrimation, blepharospasm, and mild transient conjunctival hyperemia. There is no residual discomfort or injury once it is washed away. Inhalation: May cause respiratory tract irritation. Ingestion: It may cause gastrointestinal tract irritation. It may affect behavior/central nervous system (CNS depression, general anesthetic, convulsions, seizures, somnolence, stupor, muscle contraction or spasticity, coma), brain (changes in surface EEG), metabolism, blood (intravascular hemolysis, white blood cells - decreased neutrophil function), respiration (respiratory stimulation, chronic pulmonary edema, cyanosis), cardiovascular system (hypotension, bradycardia, arrhythmias, cardiac arrest), endocrine system (hypoglycemia), urinary system (kidneys), and liver.

Chronic Potential Health Effects: Skin: Prolonged or repeated skin contact may cause allergic contact dermatitis. Ingestion: Prolonged or repeated ingestion may cause hyperglycemia and may affect behavior/CNS (symptoms similar to that of acute ingestion).

Inhalation: Prolonged or repeated inhalation may affect behavior/CNS (with symptoms similar to ingestion), and spleen.

Section 12: Ecological Information

PROPYLENE GLYCOL 57-55-6

Ecotoxicity:

Ecotoxicity in water (LC50): >5000 mg/l 24 hours [Goldfish]. >10000 mg/l 48 hours [guppy]. >10000 mg/l 48 hours [water flea].

BOD5 and COD: Not available.

Products of Biodegradation:

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

Toxicity of the Products of Biodegradation: The products of degradation are less toxic than the product itself.

Special Remarks on the Products of Biodegradation: Not available.

If applicable, IARC, NTP and OSHA carcinogens and chemicals subject to the reporting requirements of SARA Title III, Section 313 are identified in Section III with an "**". Additional ecological information is Not Determined.

Section 13: Disposal Information

WASTE DISPOSAL METHOD: Consult local authorities for proper waste disposal procedures. Empty de-pressurized containers can not be reused. Cans which are pressurized or contain liquid must be disposed of in a permitted waste management facility. Consult Federal, State, and local disposal authorities for approved procedures.



SAFETY DATA SHEET

SDS PREP DATE: 8/30/2017

SDS REVISION DATE: 6/21/2017

3137 E. 26th Street
Vernon, CA 90058
(323) 266-7111

Product ID: 57012

24-Hour Emergency Telephone: (800) 255-3924

Section 14: Transportation Information

DOT Proper Shipping Name: UN1950

Aerosols, non-flammable, (each not exceeding 1L capacity) 2.2

Section 15: Regulatory Information

	CAS#	PEL	TLV
NITROGEN	7727-37-9	N/D	N/D
INERT MATERIAL	7732-18-5	N/D	N/D
SODIUM BENZOATE	532-32-1	<NOT ESTABLISHED>	<NOT ESTABLISHED>
PROPYLENE GLYCOL	57-55-6	<NONE ESTABLISHED>	<NONE ESTABLISHED>

If applicable, IARC, NTP and OSHA carcinogens and chemicals subject to the reporting requirements of SARA Title III, Section 313 are identified above with an "*"

Section 16: Other Information

Consumer Product Safety Act Certification.

This product was evaluated by the Company listed above and is certified to be in compliance with the provisions of the Consumer Product Safety Act, the Federal Hazardous Substances Act, and the Poison Prevention Packaging Act, as applicable. This product was manufactured at the location identified on the SDS. The date of manufacture is stamped on the product container. No testing is required to certify compliance with the above mentioned regulation.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.



SAFETY DATA SHEET

3137 E. 26th Street
Vernon, CA 90058
(323) 266-7111

SDS PREP DATE: 8/30/2017

SDS REVISION DATE: 6/21/2017

Product ID: 57013

24-Hour Emergency Telephone: (800) 255-3924

This Safety Data Sheet contains environmental, health and toxicology information for your employees. Please make sure this information is given to them. It also contains information to help you meet community Right To Know emergency response reporting requirements under SARA TITLE III and many other laws. If you resell this product, this SDS must be given to the buyer or the information incorporated in your SDS.

Section 1: Company and Product Identification

Starco Brands
3137 E. 26th Street
Vernon, CA 90058
(323) 266-7111

24-Hour Emergency Telephone: (800) 255-3924

Product ID: 57013

Product Name: Breathe - Stainless Steel Cleaner (6 x 14 oz)

Intended Use: STAINLESS STEEL CLEANER

Section 2: Hazard(s) Identification

Product Signal Word: **WARNING**

Physical Hazard Classification: Aerosols, Category 3

Contains gas under pressure; may explode if heated.

Physical Hazard Precautionary Statements:

Do not pierce or burn, even after use.

Do not expose to temperatures exceeding 50 °C/122°F.



Section 3: Product Composition

	CAS#	% Range		PEL	TLV
NITROGEN	7727-37-9	1%	10%	N/D	N/D
UNSATURATED FATTY ACIDS	61788-66-7	1%	10%	NON ESTABLISHED BY OSHA	NON ESTABLISHED BY OSHA
INERT MATERIAL	7732-18-5	50%	95%	N/D	N/D
SOY BEAN OIL	8001-22-7	5%	20%	TWA: 5 mg/m3	N/D

Specific chemical identity and exact percentages are withheld as Trade Secret.

Section 4: First-Aid Measures

GENERAL: This material is an aspiration hazard and defats the skin. Breathing vapors of high concentrations may cause CNS depression.

EYE CONTACT: Slightly irritating but does not injure eye tissue.

SKIN CONTACT: Low order of toxicity. Frequent or prolonged contact may irritate and cause dermatitis. Skin contact may aggravate an existing dermatitis condition.

INHALATION: High vapor/aerosol concentrations (greater than approximately 100 ppm) are irritating to the eyes and the respiratory tract, may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death.

INGESTION: Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury,



SAFETY DATA SHEET

SDS PREP DATE: 8/30/2017

SDS REVISION DATE: 6/21/2017

3137 E. 26th Street
Vernon, CA 90058
(323) 266-7111

Product ID: 57013

24-Hour Emergency Telephone: (800) 255-3924

possibly minimal toxicity.

FIRST AID
EYE CONTACT: Flush eyes with large amounts of water until irritation subsides. If irritation persists, get medical attention.
SKIN CONTACT: Flush with large amounts of water; use soap if available. Remove grossly contaminated clothing, including shoes, and launder before reuse.
INHALATION: Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Call for prompt medical attention
INGESTION: If swallowed, DO NOT induce vomiting. Keep at rest. Get prompt medical attention.

PRECAUTIONS
SPECIAL PRECAUTIONS: Health studies have shown that many hydrocarbons pose potential human health risks which may vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized.
PERSONAL PROTECTION: For open systems where contact is likely, wear safety glasses with side shields, long sleeves, and chemical resistant gloves. Where concentrations in air may exceed the limits, work practice or other means of exposure reduction are not adequate, NIOSH/MSHA approved respirators may be necessary to prevent overexposure by inhalation.
VENTILATION: The use of mechanical dilution ventilation is recommended whenever this product is used in a confined space, is heated above ambient temperatures, or is agitated.

Section 5: Fire-Fighting Measures

FIRE AND EXPLOSION HAZARDS: This product releases Flammable Vapors at well below ambient temperatures and readily forms flammable mixtures with air exposed to an ignition source. It will burn in the open or be explosive in confined spaces. Its vapors are heavier than air and may travel long distances to a point of ignition, and then flash back. Alkaline/chlorine gas mixtures have produced explosions.

EXTINGUISHING MEDIA: Dry Chemical. CO2. Halogenated Extinguishing Agent. Stop Gas Flow.

SPECIAL FIREFIGHTING PROCEDURES: Gas fires should not be extinguished unless the gas flow can be stopped immediately. Allow the fire to burn itself out. If the source cannot be shut off immediately, all equipment and surfaces exposed to the fire should be cooled with water to prevent over-heating flash-backs, or explosions. Control fire until gas supply can be shut off. Use proper protective equipment. Use fresh air respirator when exposure to hazardous concentrations of toxic gases is possible.

FIRE FIGHTING: Use water spray to cool fire exposed surfaces and to protect personnel. Isolate "fuel" supply from fire. Use foam, dry chemical, or water spray to extinguish fire. Avoid spraying water directly into storage containers due to danger of boiling over. This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode.

Section 6: Accidental Release Measures

STEPS TO BE TAKEN IN CASE CONTAINER IS PUNCTURED AND MATERIAL IS RELEASED:
Clean up area by mopping or with absorbent materials and place in closed container for disposal. Consult Federal, State, and local disposal authorities.

WASTE DISPOSAL METHOD: Consult local authorities for proper waste disposal procedures. Empty de-pressurized containers can not be reused. Cans which are pressurized or contain liquid must be disposed of in a permitted waste management facility. Consult Federal, State, and local disposal authorities for approved procedures.

Section 7: Handling and Storage

VENTILATION REQUIREMENT: Use adequate level exhaust ventilation. Note: Where carbon monoxide may be generated, special ventilation may be required. Local exhaust recommended when appropriate to control employee exposure.

RESPIRATORY PROTECTION: Based on contamination level and working limits of the respirator, use a respirator approved by NIOSH/MSHA.

EYES: Face shield and goggles or chemical goggles should be worn.



SAFETY DATA SHEET

SDS PREP DATE: 8/30/2017

SDS REVISION DATE: 6/21/2017

3137 E. 26th Street
Vernon, CA 90058
(323) 266-7111

Product ID: 57013

24-Hour Emergency Telephone: (800) 255-3924

GLOVES: Impervious gloves should be worn. Gloves contaminated with the product should be discarded. Polyfluorinated polyethylene has been suggested.

OTHER CLOTHING EQUIPMENT: Standard work clothing. Standard work shoes; discard if shoes can not be decontaminated. Store contaminated clothing in well ventilated cabinets or closed containers. Wash contaminated clothing and dry before reuse.

RESPIRATORY PROTECTION: In situations where vapor concentrations exceed the recommended exposure limits, a NIOSH approved organic vapor cartridge or air-supplying respirator should be worn.

Section 8: Exposure Control / Personal Protection

VENTILATION REQUIREMENT: Use adequate level exhaust ventilation. Note: Where carbon monoxide may be generated, special ventilation may be required. Local exhaust recommended when appropriate to control employee exposure.

RESPIRATORY PROTECTION: Based on contamination level and working limits of the respirator, use a respirator approved by NIOSH/MSHA.

EYES: Face shield and goggles or chemical goggles should be worn.

GLOVES: Impervious gloves should be worn. Gloves contaminated with the product should be discarded. Polyfluorinated polyethylene has been suggested.

OTHER CLOTHING EQUIPMENT: Standard work clothing. Standard work shoes; discard if shoes can not be decontaminated. Store contaminated clothing in well ventilated cabinets or closed containers. Wash contaminated clothing and dry before reuse.

RESPIRATORY PROTECTION: In situations where vapor concentrations exceed the recommended exposure limits, a NIOSH approved organic vapor cartridge or air-supplying respirator should be worn.

Section 9: Product Properties

Flash Point (CCP): N/A, LVL 1 NON-FLAMMABLE AEROSOL

Boiling Point for Product: N/D

Vapor Pressure for Product: N/D

Vapor Density for Product: N/D

Specific Gravity: N/D

V.O.C.: 0% by weight

Water Solubility: PARTIALLY MISCIBLE

Appearance: AEROSOL SPRAY

PH: N/D

Section 10: Stability and Reactivity

STABILITY: Stable

CONDITIONS TO AVOID: Temperatures above 130 degree F.

HAZARDOUS POLYMERIZATION: Will not occur



SAFETY DATA SHEET

SDS PREP DATE: 8/30/2017

SDS REVISION DATE: 6/21/2017

3137 E. 26th Street
Vernon, CA 90058
(323) 266-7111

Product ID: 57013

24-Hour Emergency Telephone: (800) 255-3924

MATERIALS AND CONDITIONS TO AVOID INCOMPATIBILITY: Strong oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: None

Section 11: Toxicological Information

UNSATURATED FATTY ACIDS 61788-66-7

Acute oral toxicity: LD 50 Rat: 25,000 mg/kg

Special Remarks on Chronic Effects on Humans:

Human: passes the placental barrier, detected in maternal milk. May cause cancer based on animal test data. No human data found. May affect genetic material (mutagenic).

Special Remarks on other Toxic Effects on Humans:

Acute Potential Health Effects: Skin: Causes skin irritation. Eyes: May cause eye irritation. Ingestion: May cause digestive tract irritation. It is expected to be a low hazard for usual industrial handling. Inhalation: May cause respiratory tract irritation. It is expected to be a low hazard to usual industrial handling. Note: According the Registry of Toxic Effects of Chemicals, when Oleic acid was administered to rats and mice through intravenous injection, behavior and respiration were affected.

SOY BEAN OIL 8001-22-7

Exposure limits listed in PEL are for respirable vegetable oil mist from OSHA's 1989 air contaminants standard. These exposure limits were vacated in 1992.

Section 12: Ecological Information

If applicable, IARL, NPT and OSHA carcinogens and chemicals subject to the reporting requirements of SARA Title III, Section 313 are identified in Section III with an "**". Additional ecological information is Not Determined.

Section 13: Disposal Information

WASTE DISPOSAL METHOD: Consult local authorities for proper waste disposal procedures. Empty de-pressurized containers can not be reused. Cans which are pressurized or contain liquid must be disposed of in a permitted waste management facility. Consult Federal, State, and local disposal authorities for approved procedures.

Section 14: Transportation Information

DOT Proper Shipping Name: UN1950

Aerosols, non-flammable, (each not exceeding 1L capacity) 2.2

Section 15: Regulatory Information

	CAS#	PEL	TLV
NITROGEN	7727-37-9	N/D	N/D
UNSATURATED FATTY ACIDS	61788-66-7	NON ESTABLISHED BY OSHA	NON ESTABLISHED BY OSHA
INERT MATERIAL	7732-18-5	N/D	N/D
SOY BEAN OIL	8001-22-7	TWA: 5 mg/m3	N/D



SAFETY DATA SHEET

SDS PREP DATE: 8/30/2017

SDS REVISION DATE: 6/21/2017

3137 E. 26th Street
Vernon, CA 90058
(323) 266-7111

Product ID: 57013

24-Hour Emergency Telephone: (800) 255-3924

If applicable, IARC, NTP and OSHA carcinogens and chemicals subject to the reporting requirements of SARA Title III, Section 313 are identified above with an "**"

Section 16: Other Information

Consumer Product Safety Act Certification.

This product was evaluated by the Company listed above and is certified to be in compliance with the provisions of the Consumer Product Safety Act, the Federal Hazardous Substances Act, and the Poison Prevention Packaging Act, as applicable. This product was manufactured at the location identified on the SDS. The date of manufacture is stamped on the product container. No testing is required to certify compliance with the above mentioned regulation.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.



SAFETY DATA SHEET

SDS PREP DATE: 8/30/2017

SDS REVISION DATE: 6/21/2017

3137 E. 26th Street
Vernon, CA 90058
(323) 266-7111

Product ID: 57014

24-Hour Emergency Telephone: (800) 255-3924

This Safety Data Sheet contains environmental, health and toxicology information for your employees. Please make sure this information is given to them. It also contains information to help you meet community Right To Know emergency response reporting requirements under SARA TITLE III and many other laws. If you resell this product, this SDS must be given to the buyer or the information incorporated in your SDS.

Section 1: Company and Product Identification

Starco Brands
3137 E. 26th Street
Vernon, CA 90058
(323) 266-7111

24-Hour Emergency Telephone: (800) 255-3924

Product ID: 57014

Product Name: Breathe - Furniture Polish (6 x 14 oz)

Intended Use: FURNITURE POLISH

Section 2: Hazard(s) Identification

Product Signal Word: **WARNING**

Physical Hazard Classification: Aerosols, Category 3

Contains gas under pressure; may explode if heated.

Physical Hazard Precautionary Statements:

Do not pierce or burn, even after use.

Do not expose to temperatures exceeding 50 °C/122°F.



Section 3: Product Composition

	CAS#	% Range		PEL	TLV
NITROGEN	7727-37-9	1%	10%	N/D	N/D
UNSATURATED FATTY ACIDS	61788-66-7	1%	10%	NON ESTABLISHED BY OSHA	NON ESTABLISHED BY OSHA
INERT MATERIAL	7732-18-5	50%	95%	N/D	N/D
SODIUM BENZOATE	532-32-1	0%	3%	<NOT ESTABLISHED>	<NOT ESTABLISHED>
SOY BEAN OIL	8001-22-7	5%	20%	TWA: 5 mg/m3	N/D

Specific chemical identity and exact percentages are withheld as Trade Secret.

Section 4: First-Aid Measures

GENERAL: This material is an aspiration hazard and defats the skin. Breathing vapors of high concentrations may cause CNS depression.

EYE CONTACT: Slightly irritating but does not injure eye tissue.

SKIN CONTACT: Low order of toxicity. Frequent or prolonged contact may irritate and cause dermatitis. Skin contact may aggravate an existing dermatitis condition.

INHALATION: High vapor/aerosol concentrations (greater than approximately 100 ppm) are irritating to the eyes and the respiratory tract, may cause



SAFETY DATA SHEET

SDS PREP DATE: 8/30/2017

SDS REVISION DATE: 6/21/2017

3137 E. 26th Street
Vernon, CA 90058
(323) 266-7111

Product ID: 57014

24-Hour Emergency Telephone: (800) 255-3924

headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death.

INGESTION: Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly minimal toxicity.

FIRST AID
EYE CONTACT: Flush eyes with large amounts of water until irritation subsides. If irritation persists, get medical attention.
SKIN CONTACT: Flush with large amounts of water; use soap if available. Remove grossly contaminated clothing, including shoes, and launder before reuse.
INHALATION: Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Call for prompt medical attention
INGESTION: If swallowed, DO NOT induce vomiting. Keep at rest. Get prompt medical attention.

PRECAUTIONS
SPECIAL PRECAUTIONS: Health studies have shown that many hydrocarbons pose potential human health risks which may vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized.
PERSONAL PROTECTION: For open systems where contact is likely, wear safety glasses with side shields, long sleeves, and chemical resistant gloves. Where concentrations in air may exceed the limits, work practice or other means of exposure reduction are not adequate, NIOSH/MSHA approved respirators may be necessary to prevent overexposure by inhalation.
VENTILATION: The use of mechanical dilution ventilation is recommended whenever this product is used in a confined space, is heated above ambient temperatures, or is agitated.

Section 5: Fire-Fighting Measures

FIRE AND EXPLOSION HAZARDS: This product releases Flammable Vapors at well below ambient temperatures and readily forms flammable mixtures with air exposed to an ignition source. It will burn in the open or be explosive in confined spaces. Its vapors are heavier than air and may travel long distances to a point of ignition, and then flash back. Alkaline/chlorine gas mixtures have produced explosions.

EXTINGUISHING MEDIA: Dry Chemical. CO2. Halogenated Extinguishing Agent. Stop Gas Flow.

SPECIAL FIREFIGHTING PROCEDURES: Gas fires should not be extinguished unless the gas flow can be stopped immediately. Allow the fire to burn itself out. If the source cannot be shut off immediately, all equipment and surfaces exposed to the fire should be cooled with water to prevent over-heating flash-backs, or explosions. Control fire until gas supply can be shut off. Use proper protective equipment. Use fresh air respirator when exposure to hazardous concentrations of toxic gases is possible.

FIRE FIGHTING: Use water spray to cool fire exposed surfaces and to protect personnel. Isolate "fuel" supply from fire. Use foam, dry chemical, or water spray to extinguish fire. Avoid spraying water directly into storage containers due to danger of boiling over. This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode.

Section 6: Accidental Release Measures

STEPS TO BE TAKEN IN CASE CONTAINER IS PUNCTURED AND MATERIAL IS RELEASED:
Clean up area by mopping or with absorbent materials and place in closed container for disposal. Consult Federal, State, and local disposal authorities.

WASTE DISPOSAL METHOD: Consult local authorities for proper waste disposal procedures. Empty de-pressurized containers can not be reused. Cans which are pressurized or contain liquid must be disposed of in a permitted waste management facility. Consult Federal, State, and local disposal authorities for approved procedures.

Section 7: Handling and Storage

VENTILATION REQUIREMENT: Use adequate level exhaust ventilation. Note: Where carbon monoxide may be generated, special ventilation may be required. Local exhaust recommended when appropriate to control employee exposure.

RESPIRATORY PROTECTION: Based on contamination level and working limits of the respirator, use a respirator approved by NIOSH/MSHA.



SAFETY DATA SHEET

SDS PREP DATE: 8/30/2017

SDS REVISION DATE: 6/21/2017

3137 E. 26th Street
Vernon, CA 90058
(323) 266-7111

Product ID: 57014

24-Hour Emergency Telephone: (800) 255-3924

EYES: Face shield and goggles or chemical goggles should be worn.

GLOVES: Impervious gloves should be worn. Gloves contaminated with the product should be discarded. Polyfluorinated polyethylene has been suggested.

OTHER CLOTHING EQUIPMENT: Standard work clothing. Standard work shoes; discard if shoes can not be decontaminated. Store contaminated clothing in well ventilated cabinets or closed containers. Wash contaminated clothing and dry before reuse.

RESPIRATORY PROTECTION: In situations where vapor concentrations exceed the recommended exposure limits, a NIOSH approved organic vapor cartridge or air-supplying respirator should be worn.

Section 8: Exposure Control / Personal Protection

VENTILATION REQUIREMENT: Use adequate level exhaust ventilation. Note: Where carbon monoxide may be generated, special ventilation may be required. Local exhaust recommended when appropriate to control employee exposure.

RESPIRATORY PROTECTION: Based on contamination level and working limits of the respirator, use a respirator approved by NIOSH/MSHA.

EYES: Face shield and goggles or chemical goggles should be worn.

GLOVES: Impervious gloves should be worn. Gloves contaminated with the product should be discarded. Polyfluorinated polyethylene has been suggested.

OTHER CLOTHING EQUIPMENT: Standard work clothing. Standard work shoes; discard if shoes can not be decontaminated. Store contaminated clothing in well ventilated cabinets or closed containers. Wash contaminated clothing and dry before reuse.

RESPIRATORY PROTECTION: In situations where vapor concentrations exceed the recommended exposure limits, a NIOSH approved organic vapor cartridge or air-supplying respirator should be worn.

Section 9: Product Properties

Flash Point (CCP): N/A, LVL 1 NON-FLAMMABLE AEROSOL

Boiling Point for Product: N/D

Vapor Pressure for Product: N/D

Vapor Density for Product: N/D

Specific Gravity: N/D

V.O.C.: 0% by weight

Water Solubility: MISCIBLE

Appearance: AEROSOL SPRAY

PH: N/D

Section 10: Stability and Reactivity

STABILITY: Stable

CONDITIONS TO AVOID: Temperatures above 130 degree F.



SAFETY DATA SHEET

SDS PREP DATE: 8/30/2017

SDS REVISION DATE: 6/21/2017

3137 E. 26th Street
Vernon, CA 90058
(323) 266-7111

Product ID: 57014

24-Hour Emergency Telephone: (800) 255-3924

HAZARDOUS POLYMERIZATION: Will not occur

MATERIALS AND CONDITIONS TO AVOID INCOMPATIBILITY: Strong oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: None

Section 11: Toxicological Information

UNSATURATED FATTY ACIDS 61788-66-7

Acute oral toxicity: LD 50 Rat: 25,000 mg/kg

Special Remarks on Chronic Effects on Humans:

Human: passes the placental barrier, detected in maternal milk. May cause cancer based on animal test data. No human data found. May affect genetic material (mutagenic).

Special Remarks on other Toxic Effects on Humans:

Acute Potential Health Effects: Skin: Causes skin irritation. Eyes: May cause eye irritation. Ingestion: May cause digestive tract irritation. It is expected to be a low hazard for usual industrial handling. Inhalation: May cause respiratory tract irritation. It is expected to be a low hazard to usual industrial handling. Note: According the Registry of Toxic Effects of Chemicals, when Oleic acid was administered to rats and mice through intravenous injection, behavior and respiration were affected.

SODIUM BENZOATE 532-32-1

Acute oral toxicity: LD 50 Rat: 4070 mg/kg

May aggravate existing skin conditions, exposure may cause redness and irritation to skin, respiratory system, eyes, and gastrointestinal tract.

SOY BEAN OIL 8001-22-7

Exposure limits listed in PEL are for respirable vegetable oil mist from OSHA's 1989 air contaminants standard. These exposure limits were vacated in 1992.

Section 12: Ecological Information

If applicable, IARL, NPT and OSHA carcinogens and chemicals subject to the reporting requirements of SARA Title III, Section 313 are identified in Section III with an "*". Additional ecological information is Not Determined.

Section 13: Disposal Information

WASTE DISPOSAL METHOD: Consult local authorities for proper waste disposal procedures. Empty de-pressurized containers can not be reused. Cans which are pressurized or contain liquid must be disposed of in a permitted waste management facility. Consult Federal, State, and local disposal authorities for approved procedures.

Section 14: Transportation Information

DOT Proper Shipping Name: UN1950

Aerosols, non-flammable, (each not exceeding 1L capacity) 2.2

Section 15: Regulatory Information

	CAS#	PEL	TLV
NITROGEN	7727-37-9	N/D	N/D



SAFETY DATA SHEET

SDS PREP DATE: 8/30/2017

SDS REVISION DATE: 6/21/2017

3137 E. 26th Street
Vernon, CA 90058
(323) 266-7111

Product ID: 57014

24-Hour Emergency Telephone: (800) 255-3924

UNSATURATED FATTY ACIDS	61788-66-7	NON ESTABLISHED BY OSHA	NON ESTABLISHED BY OSHA
INERT MATERIAL	7732-18-5	N/D	N/D
SODIUM BENZOATE	532-32-1	<NOT ESTABLISHED>	<NOT ESTABLISHED>
SOY BEAN OIL	8001-22-7	TWA: 5 mg/m3	N/D

If applicable, IARL, NPT and OSHA carcinogens and chemicals subject to the reporting requirements of SARA Title III, Section 313 are identified above with an "*"

Section 16: Other Information

Consumer Product Safety Act Certificaton.

This product was evaluated by the Company listed above and is certified to be in compliance with the provisions of the Consumer Product Safety Act, the Federal Hazardous Substances Act, and the Poison Prevention Packaging Act, as applicable. This product was manufactured at the location identified on the SDS. The date of manufacture is stamped on the product container. No testing is required to certify compliance with the above mentioned regulation.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.